

# iCombi® Pro.

## Modellenoverzicht

Te bestellen van vanaf 6 mei 2020



iCombi Pro	XS 6-2/3	6-1/1	10-1/1	6-2/1	10-2/1	20-1/1	20-2/1
Capaciteit	6 × 2/3 GN	6 × 1/1 GN	10 × 1/1 GN	6 × 2/1 GN	10 × 2/1 GN	20 × 1/1 GN	20 × 2/1 GN
Aantal maaltijden per dag	20–80	30–100	80–150	60–160	150–300	150–300	300–500
Lading in de lengte (GN)	1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1 GN	2/1, 1/1 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	2/1, 1/1 GN
Breedte	655 mm	850 mm	850 mm	1072 mm	1072 mm	877 mm	1082 mm
Diepte	621 mm	842 mm	842 mm	1042 mm	1042 mm	913 mm	1117 mm
Hoogte	567 mm	754 mm	1014 mm	754 mm	1014 mm	1807 mm	1807 mm
Aansluiting water	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"
Afvoer water	DN 40	DN 50	DN 50	DN 50	DN 50	DN 50	DN 50
Waterdruk	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar	1,0 - 6,0 bar
<b>Elektrisch</b>							
Gewicht	67 kg	99 kg	127 kg	137 kg	179 kg	263 kg	336 kg
Aansluitwaarde	5.7 kW	10.8 kW	18.9 kW	22.4 kW	37.4 kW	37.2 kW	67.9 kW
Zekering	3 × 10 A	3 × 16 A	3 × 32 A	3 × 35 A	3 × 63 A	3 × 63 A	3 × 100 A
Aansluiting	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V
Output convectie modus	5.4 kW	10.25 kW	18 kW	21.6 kW	36 kW	36 kW	66 kW
Output stoom modus	5.4 kW	9 kW	18 kW	18 kW	36 kW	36 kW	54 kW
<b>Gas</b>							
Gewicht		117 kg	155 kg	144 kg	192 kg	284 kg	379 kg
Aansluitwaarde elektrisch systeem		0.6 kW	0.9 kW	0.9 kW	1.5 kW	1.3 kW	2.2 kW
Zekering		1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A
Aansluiting		1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V
Gas aansluiting		3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG	3/4" IG
<b>Gas /LPG G31/LPG G30*</b>							
Max. nominaal thermische waarde		13 kW/13 kW/ 13.5 kW	22 kW/22 kW/ 23 kW	28 kW/28 kW/ 29.5 kW	40 kW/40 kW/ 42 kW	42 kW/42 kW/ 44 kW	80 kW/80 kW/ 84 kW
Output convectie modus		13 kW/13 kW/ 13.5 kW	22 kW/22 kW/ 23 kW	28 kW/28 kW/ 29.5 kW	40 kW/40 kW/ 42 kW	42 kW/42 kW/ 44 kW	80 kW/80 kW/ 84 kW
Output stoom modus		12 kW/12 kW/ 12.5 kW	20 kW/20 kW/ 21 kW	21 kW/21 kW/ 22 kW	40 kW/40 kW/ 42 kW	38 kW/38 kW/ 40 kW	51 kW/51 kW/ 53.5 kW

\* To guarantee proper operation, the appropriate connection flow pressure must be ensured:  
Natural gas H G20 18 25 mbar (0.261 0.363 psi), Natural gas L G25: 20 30 mbar (0.290 0.435 psi), LPG G30 und G31: 25 57,5 mbar (0.363 0.834 psi).

RATIONAL België  
Westpoort 62  
2070 Zwijndrecht

T: 03 760 03 70  
info@rational.be  
www.rational.be

